



Unbeatable Performance F-203 2K Through Black Car Paint For Long-Lasting Results

Our Product Introduction

for more products please visit us on refinishcarpaint.com

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: F-203
- Minimum Order Quantity: 200L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Box/Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 200L per day



Product Specification

- Brand: Faralli
- Code: F-203
- Product Name: 2K Through Black
- Recoat: 2 Hours
- Uv Protection: Yes
- Number Of Coats: 2-3
- Chemical Resistance: Strong
- Storage: Store In A Cool, Dry Place
- Suitable Surfaces: Metal, Plastic, Fiberglass
- Sheen: High
- Easy To Clean: Yes
- Resistance: Various Resistance
- Scratch Resistance: High
- Highlight: **2K Through Black Car Paint, Long-Lasting Results Car Paint, Unbeatable Performance Car Paint**



More Images



Product Description

Unbeatable Performance F-203 2K Through Black Car Paint for Long-Lasting Results

Faralli by Meklon: The Premier Choice for Automotive Refinishing

Faralli, the flagship brand of Meklon, stands at the forefront of the automotive refinishing industry, offering a comprehensive tinting system and a robust lineup of refinish products and auxiliaries. Our extensive range includes 1K basecoats, 2K topcoats, clear coats, hardeners, thinners, 2K primers, putties, and a variety of auxiliaries, all designed to deliver tailored solutions that meet the exacting standards of our customers.

Introducing Faralli's Through Black Auto Coat

Black, a timeless and universally admired hue, remains a quintessential choice for automotive aesthetics, exuding sophistication and a refined elegance. Faralli's Through Black Auto Coat is a testament to this classic appeal, featuring a rich, deep black finish that boasts a high-gloss luster, enhancing the visual impact of any vehicle.

Key Features:

Purity of Color: Our Through Black Auto Coat is a solid black, devoid of any metallic or pearl additives, ensuring a pure, unadulterated black finish that commands attention.

High-Gloss Finish: The paint's exceptional gloss level imparts a mirror-like smoothness, reflecting light to create a captivating depth and a luxurious appearance.

Ideal for professional refinishers seeking to restore or enhance a vehicle's original allure, Faralli's Through Black Auto Coat is the epitome of automotive elegance. Experience the transformative power of a paint that not only restores but also elevates the visual appeal of your vehicle to new heights of sophistication.

Expertise and Excellence:

At Meklon, we are committed to providing the highest quality products and services. Our Faralli brand is a reflection of this commitment, offering a suite of refinishing solutions that cater to the diverse needs of the automotive industry.

Connect with Us:

For inquiries or to experience the superior results of Faralli's Through Black Auto Coat, please contact our sales team. Discover how our professional-grade products can revitalize your vehicle with a touch of timeless elegance.

| | | | |
|----------------------|--|-----------------------|------------------------------------|
| Product Name: | F-203 2K Through Black | Specifications: | 1L/4L/5L |
| Features: | high covering power, high temperature resistance | Scope of application: | Cars, ships, vehicle, tanks |
| Color: | Through Black | Voc: | Low |
| Storage method: | Store in a cool, dry, ventilated and dark place | Sales scope: | global |
| Drying time: | surface drying time is 2 hours, actual drying time is 24 hours | Mixing ratio: | paint:curing agent:thinner=2:1:0.3 |
| Substrate treatment: | Before spraying the substrate, the substrate must be cleaned, degreased with degreaser, and polished with 800#~1000# sandpaper. Clean it after polishing, and use degreaser to remove oil again. | | |
| Process: | The spraying process uses wet spraying to spray 2 to 3 layers on the surface of the substrate. Pay attention to leaving 5 to 10 minutes of evaporation time between each two layers. After spraying, the paint film needs to stand for 10 to 15 minutes. Then bake. Thickness in dry film state: 35~50 microns | | |

At Meklon, under the esteemed Faralli brand, we pride ourselves on delivering a suite of competitive strengths that set us apart in the automotive refinishing industry:

Consistency and Reliability: Our tinting system is renowned for its stability and unwavering quality, ensuring that every refinishing project meets the highest standards of excellence.

Extensive Color Palette: With a vast library of over 30,000 color formulas at our disposal, we offer unparalleled color matching capabilities, guaranteeing a perfect match for any vehicle.

Innovative Development: Our commitment to innovation is unceasing. We continuously develop new formulas and offer bespoke color customization services to meet the unique needs of our clients.

Comprehensive Color Tools: Our arsenal includes OEM and variant color chips, among other advanced color tools, facilitating precise color selection and application.

Exceptional After-Sales Support: Our dedication extends beyond the sale. We provide comprehensive on-site technical training and a variety of promotional materials, including posters, T-shirts, caps, and mixing machines, to support our clients' success.

Elevating Your Refinishing Experience:

Meklon's Faralli is more than just a product line; it's a commitment to professional refinishers seeking the pinnacle of quality, innovation, and support. Our products are engineered to deliver superior results, ensuring that every vehicle restoration or enhancement project is executed with the utmost precision and aesthetic appeal.

Raw materials

In order to ensure the quality and stable colors, our raw material are mainly purchased from BASF, MERCK, ECKART, EASTMAN, DSM, BYK and BAYER etc. Being the strategic partner of BASF, we are the best Chinese buyer of their raw

materials.

Our advantage

Durability: Our black automotive paint offers exceptional durability, resisting the elements of daily use such as scratches, stone strikes and UV radiation. This helps protect the body from damage and extends the life of the coating.

Easy to apply: Our black car paint is designed to be easy to apply, whether it is a professional painter or a car owner doing DIY painting themselves, they can get excellent painting results. It can be applied by spray or brush and has a short drying time.

Color Stability: Our black car paint has good color stability, keeping the color vibrant and consistent for a long time. This means that it will not show noticeable fading or discoloration even after a period of exposure to sunlight.

Optional effects: In addition to the traditional black high-gloss paint job, we also offer other black effect options such as metallic black, pearl black or matte black. These effects can add a unique look to your car and can be chosen based on personal preference.

Preparation for spray paint:

Make sure the work area is well ventilated and wear appropriate personal protective equipment such as a respirator, gloves and goggles.

Gather the materials and tools you need, including plain black paint, thinner, stir stick, weighing equipment, spray gun, and cleaning supplies.

Mixing and blending:

Determine the mixing ratio of pure black paint according to the recipe or guidance provided in the Meklon instructions. This is usually expressed as volume percent or mass percent.

Pour the desired amount of pure black paint into the container.

Follow the recipe and gradually add the appropriate amount of diluent. Note, be careful when adding diluent to avoid too low or too high a color concentration.

Use a stir stick to mix thoroughly to ensure that the pigment and thinner are fully and evenly mixed together.

Preparation for spraying:

Clean and prepare surfaces for spraying. Make sure the surface is smooth and free of oil, dust or other impurities. Surface preparation can be done using appropriate cleaners and sandpaper.

Mask the surrounding area to prevent paint splatter or contamination during spraying.

Spraying process:

Adjust the spray gun pressure and nozzle size to suit the required coating thickness and spray area, and determine the spray distance and angle. Use even and overlapping spray motions, maintaining a consistent speed and pressure to ensure an even coat with no drips or sags. After each spray application, allow appropriate drying time and apply additional coats or touch-ups as needed.

Finish and clean:

After finishing spraying, check the quality and appearance of the coating. If necessary, grinding, polishing or other repair work can be performed.

To clean spray guns and tools, use the entire Meklon system.

Factory Tour:



Effect picture:



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province