



1K 2K Solid Color Car Paint Automotive Paint Car Scratch Repair Car Paint Top Coat Supplier

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: P-2002
- Minimum Order Quantity: 200L
- Price: 4.64USD/L-6.92USD/L
- Packaging Details: Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500L per day



Product Specification

- Brand: PORSHICHE
- Name: White
- Cleanup: Soap And Water
- Coverage: 400 Sq. Ft. Per Gallon
- Finish: Glossy
- Indoor/Outdoor: Indoor And Outdoor
- Number Of Coats: 2
- Surface: Wood, Metal, Masonry, And More
- UV Resistant: Yes
- VOC Level: Low
- Highlight: Automotive Solid Color Car Paint,
2K Solid Color Car Paint,
Scratch Repair Solid Color Car Paint



Product Description

1K 2K Solid Color Car Paint Automotive Paint Car Scratch Repair Car Paint Top Coat Supplier

Product Description:

Meklon's Pristine White: A Timeless Classic

Meklon's Pristine White automotive paint offers a clean, elegant, and timeless finish. This classic color is a versatile choice for any vehicle, providing a blank canvas for customization and personalization.

Key Features and Benefits:

Brilliant White Finish: Our advanced pigment technology delivers a pure, bright white that exudes elegance.

Superior Durability: Our 2K formula ensures exceptional resistance to scratches, chips, fading, and weathering.

Excellent Weather Resistance: Withstands the harshest weather conditions, including UV radiation, temperature fluctuations, and inclement weather.

Smooth, High-Gloss Finish: Achieve a flawless, mirror-like finish with our superior leveling properties.

Easy Application: Our user-friendly formulation is designed for efficient application, even for DIY enthusiasts.

Environmental Friendliness: Our low-VOC formula minimizes environmental impact and promotes sustainable practices.

Product Name:	P-2002 white 2K	Specifications:	1L/4L/5L
Features:	Durable, anti-corrosion, anti-rust and high sun protection	Scope of application:	Cars, ships, airplanes, tanks
Color:	Support color correction		
Drying time::	surface drying time is 2 hours, actual drying time is 24 hours	Mixing ratio:	paint:curing agent:thinner=2:1:0.3
Storage method:	Store in a cool, dry, ventilated and dark place	Sales scope:	global



Product performance and construction:

construction substrate:	A. Original paint layer;	B. Old car paint film;	C. Intermediate paint film; Note that the construction substrate needs to be carefully polished, the surface is dry and in good condition
Substrate treatment:	Before spraying the substrate, the substrate must be cleaned, degreased with degreaser, and polished with 800#~1000# sandpaper. Clean it after polishing, and use degreaser to remove oil again.		
Construction ratio:	Temperature 15 Color paint 100 parts MK12X quick-drying hardener agent 50 parts MK602 quick-drying thinner 15-30 parts	Temperature 15 -30 Color paint 100 parts P-12X standard hardener 50 parts P-602 standard diluent 15-30 parts	
	Temperature 30 Color paint 100 parts 12X slow drying hardener 50 parts 602 slow drying thinner 15-30 parts		

Viscosity:	16 seconds to 19 seconds, spray 4# viscosity cup (at normal temperature)				
Process::	The spraying process uses wet spraying to spray 2 to 3 layers on the surface of the substrate. Pay attention to leaving 5 to 10 minutes of evaporation time between each two layers. After spraying, the paint film needs to stand for 10 to 15 minutes. Then bake. Thickness in dry film state: 35~50 microns				
Re-construction:	After spraying, any areas with particles and sags should be wet-smoothed and polished with 2000# sandpaper after they are completely hardened.				
spray tools:	Gravity spray gun (top pot) 1.2-1.5mm 3-5kg/cm ²				
	Suction spray gun (bottom) 1.4-1.6mm 3-5kg/cm ²				
Use time after mixing:	After mixing the components, they need to be used within 4 hours				
Usage amount:	The thickness of a single coating is 35 microns. The paint is calculated based on a conversion rate of 70%. The theoretical value of the mixed paint spray area is: 8 square meters/liter, and the original unmixed 13 square meters/liter.				
Drying time:	ambient temperature	Non-stick time	Dry to touch time	Available assembly time	Complete drying time
	Normal temperature 25	40 minutes	2 hours	9 hours	6 days
	Bake at 70	5 minutes	10 minutes	25 minutes	50minutes
Product expiration date:	Validity period of 1-3 years, the product should be placed in a cool and dry place at 20				
Product packaging specifications:	1L×12 cans/box; 4L×4 cans/box;5L×4 cans/box				

Precautions:

1. Before spraying, the substrate must be degreased with a degreaser, sanded and dried.
2. If the temperature of the construction environment is high, >30°C, an appropriate amount of anti-white water can be added to the diluent.
3. After mixing each component, use it up as soon as possible and do not save it for further use.
4. After spraying, the tools should be cleaned with thinner in time.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province