

# Trending Sunny Yellow High Gloss Fast Drying Car Paint

#### **Basic Information**

- Place of Origin:
- Brand Name:
- Meklon

China

- Certification: ISO,MSDS,SGS
- Model Number:
- Minimum Order Quantity:
- Price:
- Packaging Details:
- Delivery Time:
- Supply Ability:
- 50L 2.73USD/L-5.56USD/L Box/Carton
- 10-15 Work Day

Yes

Car Color


lity: 500L per day



## **Product Specification**

- Top Coat Required:
- Color:
- Formula:
- Suitable Surfaces:
- Weather Resistance:
- Uv Protection:
- Series:
- Uv Resistant:
- Specification:
- Storage:
- Bmw:

Multiple Color Options
Mekloncolormix
Metal, Plastic, And Fiberglass
High
Yes
CarCharm Series
Yes
1LX12





## More Images



## **Product Description**

Detail ed	Detailed description
Produ	The popular high gloss sunshine yellow car paint is designed for
ct	customers who pursue a bright and energetic appearance. It combines
Positi	high glossiness and fast drying characteristics, and is suitable for all
on	vehicle refurbishment/modification
Core Sellin g Point s	High gloss dazzling: Glossy paint surface has a reflectivity of ≥ 90%, presenting a mirror like transparent texture, making it even more dazzling under sunlight, with strong visual impact. Fast Drying: With the support of Fast Drying technology, surface drying only takes 5-8 minutes (20-25 environment), and hard drying takes 2-3 hours, greatly reducing the construction period and suitable for batch operations or emergency repairs. Weather resistant protection: Built in UV stabilizer, excellent UV resistance, long-term exposure without fading or yellowing, maintaining brightness for 3 years+.
	Full model exterior painting, partial repair, sports modification, and original factory level high gloss decoration of the new car
recn nical Para	Surface drying: 5-8 minutes (room temperature 20-25, humidity $\leq$ 60%) Hard drying: 2-3 hours (light touch, non stick to hands) Complete curing: 24 hours (achieving optimal hardness and weather resistance) -Construction method: Suitable for spray gun spraying (recommended) or rolling coating (special requirements) -Film thickness: It is recommended to apply a single layer thickness of 15- 20 $\mu$ m and a total thickness of 30-40 $\mu$ m (2-3 thin layers for better coating effect) -VOC content: $\leq$ 350g/L (in compliance with international environmental standards)

#### Our full product ranges include the following:

- 1.Car Paint 2K Topcoat solid colors
- 2.Car Paint 1K basecoat metallic colors
- 3. Auto Paint 2K high solid and standard clear coat
- 4. Auto putty
- 5. Automotive 2K primers and 1K primer
- 6. Automotive Paint Binders and fixatives
- 7. Automotive Paint Related hardener, thinner and other solvent



Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province