



Fast Drying And Efficient Deep Blue Metallic Paint That Matches The Original Factory Color For Car Spray Painting

Our Product Introduction

Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Model Number: Ferrari
- Minimum Order Quantity: 50L
- Price: 2.73USD/L-5.56USD/L
- Packaging Details: Box/Carton
- Delivery Time: 10-15 Work Day
- Payment Terms: T/T
- Supply Ability: 500L per day



Product Specification

- Application Area: Chemical
- Main Raw Materials: Resine, Solvent, Pigment, LPG
- Formula: Mekloncolormix
- Scrub Resistance: Yes
- High Light: 2k Top Coat
- Recoat Time: 24 Hours
- Manufacture: Meklon
- Net Weight: 0.95KG
- Weather Resistance: Yes
- Scratch Resistant: Yes



More Images



Product Description

Overview of Meklon Automotive Repair Paint Product Line

1. Primer series

F-506 two-component intermediate primer: high filling power, suitable for metal/plastic substrates, improves the adhesion and flatness of the topcoat.

F-508 epoxy primer: super rust proof, salt spray resistant, suitable for surface pretreatment of bare metal (steel/aluminum).

F-501 plastic primer: specially designed for PP/ABS and other plastic parts to enhance the adhesion of the paint film.

2. Color paint series

1K Basecoat: Single component fast drying, containing metallic/pearl effect colors, supporting OEM color matching.

2K Topcoat: Two component high hardness, UV resistance, and long-lasting bright colors.

3. Clear varnish series

F-8000 environmentally friendly varnish: low VOC, high gloss ($\geq 95\text{GU}$), resistant to chemical corrosion.

F-8050 high gloss varnish: mirror effect, fast drying (can be polished in 20 minutes), suitable for luxury car repair.

F-8300 Silver Diamond Varnish: Contains nanoparticles, scratch resistant, suitable for high wear areas.

4. Auxiliary materials and tools

Spray gun: RP/HVLP model (1.3mm-1.8mm caliber), suitable for different viscosity coatings.

Sandpaper: All models from 60 # to 2000 #, available for dry grinding or water grinding.

Shielding materials: high temperature resistant tape (100 °C), masking paper, protective film.

5. Functional additives

F-511 drying agent: accelerates the curing of 2K paint and is essential in low-temperature environments.

F-515 anti white water: prevents paint film atomization, suitable for high humidity environments.

F-134 matting agent: customized matte effect, adjustable ratio of 5% -30%.

6. Putty and filling

F-512 atomic ash: fast drying type, crack resistant, suitable for filling deep dents.

P-550R fiber putty: lightweight and high-strength, used for repairing plastic parts such as bumpers.



Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province