

High Grade Mud Yellow Putty: High-Quality Flawless And Efficient Surface Treatment

Basic Information

Place of Origin: GUANGDONG CHINA

Brand Name: Meklon

Certification: ISO,SGS,MSDS

• Minimum Order Quantity: 50L

Price: USD2-2.9/Piece
 Packaging Details: Can/Carton
 Delivery Time: 5-8 work days

• Payment Terms: T/T

• Supply Ability: 500000Boxes/Month



Product Specification

• Water Resistant:

Shelf Life: 1-2 YearsProductname: Putty

Package Size: Varies By ProductUsage: Car Paint, Plastic Coating

Usage: Car PaiNet Weigh: 0.95KG

• Storage: Store In A Cool, Dry Place

Professional Quality: Provides Professional Quality Finish

Yes



More Images



Our high - grade putty is a top - tier product designed for both professional and DIY enthusiasts. Whether you are working on home renovation, furniture repair, or automotive touch - ups, this putty is the perfect choice.

Exceptional Quality: Formulated with high - quality ingredients, our putty offers superior adhesion and smoothness. It can effectively fill in scratches, dents, and holes, creating a seamless surface that is ready for painting or further finishing.

Easy to Use: With its user - friendly consistency, this putty is a breeze to apply. You can easily spread it using a putty knife or your preferred tool, and it dries quickly to a hard, durable finish. The included container makes it convenient for storage and transportation.

Versatile Application: Suitable for a wide range of surfaces including wood, metal, drywall, and plastic. It can be sanded down to a fine finish, allowing for precise and detailed work.

Affordable Luxury: our high - grade putty offers excellent value for money. You don't have to break the bank to achieve professional - quality results. Upgrade your surface finishing projects with our high - grade putty today!

•	1 , 10 ,
Charater astic	Easy to scratch, quick drying at room temperature, easy to sand, strong adhesion, high temperature resistance, strong filling ability, no cracking, no shrinkage, good compatibility and other advantages.
Application	Various metal surfaces, various primers and old paint surfaces, etc.
Quality Guarant ee Period	12 months in its original sealed container at 20 in a cool and dry place.
Method	Mix the main putty and hardener in proportion and complete it within the gel time. Scratched and polished putty Two component primer or treated substrate surface. If a thick coating is required, it is best to scrape it several times. If bubbles appear during the coating process, they must be thoroughly scraped with a scraper.







Guangzhou Meklon Chemical Technology Co., Ltd.



+8613392100968



Meklonpaint@gzmeklon.com



refinishcarpaint.com

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province