



## Sheet Metal Atomic Ash High-temperature Resistant Multifunctional Fiber Ash

Our Product Introduction

for more products please visit us on [refinishcarpaint.com](http://refinishcarpaint.com)

### Basic Information

- Place of Origin: China
- Brand Name: Meklon
- Certification: ISO,MSDS,SGS
- Minimum Order Quantity: 100Boxes
- Price: 2.21~6.92USD
- Packaging Details: Can/Carton;1L/4L/5L/20L/200L
- Delivery Time: 7~15 Working days
- Payment Terms: T/T
- Supply Ability: 500Boxes/day

**Product Features**  
Super strong adhesion  
Outstanding construction performance and good filling performance  
Good flexibility, quick drying, easy to polish



### Product Specification

- Formula Color App: Meklonpaintmix
- Recoat: 2 Hours
- Style Selection: Thickened And Ordinary
- Filterability: Excellent
- Curing Time: Varies By Product
- Coats Required: 2-3
- Durability: High Resistance To Weather And UV
- Scratch Resistance: Yes
- Drying Time: 15-30 Minutes (touch Dry)
- Suitable For: Cars, Trucks, Motorcycles
- Product Name: Refinish Car Paint

### Color matching system



### More Images



## Product Description

### Sheet Metal Atomic Ash, High-temperature Resistant Multifunctional Fiber Ash---High Cost-Effective Price

#### Product Features

High temperature resistance up to 180 , suitable for repairing high-temperature components such as engine compartment surroundings and exhaust pipe areas  
 Adding glass fiber reinforcement increases tensile strength by 40% and provides excellent impact resistance  
 Quick drying formula, initial curing in 20 minutes, can be polished in 2 hours  
 Suitable for various metal substrates such as steel, aluminum, galvanized sheet, etc

#### Cost effectiveness advantage

The price is only 60% -70% of imported similar products  
 The single filling thickness can reach 5mm, reducing the number of construction layers

#### Applicable scenarios

Repair of dents in automotive sheet metal (including high-temperature areas)  
 Shaping of exhaust pipe bracket, engine guard plate and other components  
 Partial reinforcement and repair of commercial vehicle frames

#### Technical parameters

Working temperature: -30 ~180 (short-term 200 )  
 Adhesion:  $\geq 3.5\text{MPa}$   
 Shrinkage rate:  $<0.8\%$   
 Packaging: 2kg/4kg/20kg

This product has passed ISO9001 quality system certification and provides technical guidance and construction training support.



**Guangzhou Meklon Chemical Technology Co., Ltd.**



+8613392100968



[Meklonpaint@gzmeklon.com](mailto:Meklonpaint@gzmeklon.com)



[refinishcarpaint.com](http://refinishcarpaint.com)

Room 1309, Tower B, Jiada International, Guangyun Road, Baiyun District, Guangzhou City, Guangdong Province